



**FIG. 100**

**Split Ring Extension Hanger**

**SERVICE:** For suspension of non-insulated, stationary piping services.

**MATERIAL:** Malleable Iron or 304 Stainless Steel

**FINISH:** Black or Electro-Galvanized

**STANDARDS:** MSS SP-58 Type 12, FS WW-H-171E Type 25

**ORDERING:** Specify figure number, pipe size, material and finish.



PIPE SIZE	PIPE OD	SCREW	A	B	C	D	WEIGHT EACH, LBS.	MAX REC. LOAD, LBS.
3/8	0.675	10 - 24	3/8	11/16	1 <sup>13</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>16</sub>	0.08	180
1/2	0.840	10 - 24	3/8	3/4	2 <sup>1</sup> / <sub>8</sub>	1 <sup>3</sup> / <sub>16</sub>	0.10	180
3/4	1.050	10 - 24	3/8	7/8	2 <sup>1</sup> / <sub>2</sub>	1 <sup>9</sup> / <sub>16</sub>	0.11	180
1	1.315	10 - 24	3/8	1 <sup>1</sup> / <sub>8</sub>	2 <sup>3</sup> / <sub>4</sub>	2	0.15	180
1 <sup>1</sup> / <sub>4</sub>	1.660	10 - 24	3/8	1 <sup>5</sup> / <sub>16</sub>	3 <sup>3</sup> / <sub>16</sub>	2 <sup>3</sup> / <sub>8</sub>	0.18	180
1 <sup>1</sup> / <sub>2</sub>	1.900	10 - 24	3/8	1 <sup>7</sup> / <sub>16</sub>	3 <sup>3</sup> / <sub>8</sub>	2 <sup>5</sup> / <sub>8</sub>	0.21	180
2	2.375	10 - 24	3/8	1 <sup>5</sup> / <sub>8</sub>	3 <sup>15</sup> / <sub>16</sub>	3 <sup>1</sup> / <sub>16</sub>	0.30	180
2 <sup>1</sup> / <sub>2</sub>	2.875	1/4	1/2	2 <sup>1</sup> / <sub>8</sub>	5 <sup>3</sup> / <sub>16</sub>	3 <sup>13</sup> / <sub>16</sub>	0.58	300
3	3.500	1/4	1/2	2 <sup>1</sup> / <sub>2</sub>	5 <sup>11</sup> / <sub>16</sub>	4 <sup>5</sup> / <sub>8</sub>	0.71	300
4	4.500	1/4	1/2	2 <sup>7</sup> / <sub>8</sub>	6 <sup>3</sup> / <sub>4</sub>	5 <sup>9</sup> / <sub>16</sub>	1.02	300

**NOTE:** Sizes 1/4", 3/8", 2 1/2", 3" and 4" are only available in hinged style, with the exception of stainless steel which is only available in two-screw style regardless of size.

