



FIG. 100

Split Ring Extension Hanger for Copper Tubing

- SERVICE:** For suspension of non-insulated, stationary copper tubing services.
- MATERIAL:** Malleable Iron
- FINISH:** Copper Epoxy Coated (COPPER-GARD)
- STANDARDS:** MSS SP-58 Type 12, FS WW-H-171E Type 25
- ORDERING:** Specify figure number, tube size and finish.



TUBE SIZE	TUBE OD	SCREW	A	B	C	D	WEIGHT EACH, LBS.	MAX REC. LOAD, LBS.
1/4	0.375	10 - 24	3/8	9/16	1 3/4	7/8	0.07	180
3/8	0.500	10 - 24	3/8	5/8	1 3/4	1 1/16	0.08	180
1/2	0.625	10 - 24	3/8	11/16	1 7/8	1 1/8	0.09	180
3/4	0.875	10 - 24	3/8	13/16	2 1/4	1 3/8	0.10	180
1	1.125	10 - 24	3/8	15/16	2 1/2	1 5/8	0.13	180
1 1/4	1.375	10 - 24	3/8	1 1/16	2 7/8	1 7/8	0.14	180
1 1/2	1.625	10 - 24	3/8	1 3/16	3	2 3/16	0.18	180
2	2.125	10 - 24	3/8	1 7/16	3 1/2	2 11/16	0.23	180
2 1/2	2.625	1/4	1/2	1 7/8	4 15/16	2 7/16	0.45	300
3	3.125	1/4	1/2	2 1/8	5 1/2	4 1/16	0.66	300
4	4.125	1/4	1/2	2 5/8	6 5/8	5 1/16	0.75	300

NOTE: Sizes 1/4", 3/8", 2 1/2", 3" and 4" are only available in hinged style.

