



FIG. 215

Adjustable Clevis Hanger for DI Pipe

SERVICE: For the suspension of non-insulated, stationary ductal iron piping services.
MATERIAL: Carbon Steel or 304/316 Stainless Steel
FINISH: Black or Hot-Dip Galvanized
STANDARDS: MSS SP-58 Type 1, FS WW-H-171E Type 1
ORDERING: Specify figure number, pipe size, material and finish.



DI PIPE SIZE	A	STOCK SIZE		B	C	E	F	BOLT	WEIGHT EACH, LBS.	MAX. REC. LOAD, LBS.
		TOP	BOTTOM							
4	5/8	8ga x 1 ³ / ₁₆	10ga x 1 ³ / ₁₆	6	8 ¹ / ₂	4 ⁵ / ₈	2 ¹ / ₈	3/8	1.32	1430
6	3/4	3ga x 1 ¹ / ₂	8ga x 1 ¹ / ₂	6 ¹³ / ₁₆	10 ¹ / ₈	5 ³ / ₁₆	1 ³ / ₄	1/2	2.86	1940
8	3/4	3ga x 1 ³ / ₄	8ga x 1 ³ / ₄	8 ⁵ / ₁₆	13	6 ⁷ / ₈	1 ⁷ / ₈	5/8	4.56	2000
10	7/8	3/8 x 1 ³ / ₄	3ga x 1 ³ / ₄	10 ¹ / ₂	16 ¹ / ₄	8 ¹ / ₂	2 ¹ / ₄	3/4	8.70	3600
12	7/8	3/8 x 2	3ga x 2	11 ³ / ₄	18 ³ / ₄	9 ³ / ₄	2 ¹³ / ₁₆	3/4	11.08	3800
14	1	1/2 x 2 ¹ / ₂	1/4 x 2 ¹ / ₂	13 ¹⁵ / ₁₆	21 ¹⁵ / ₁₆	11 ¹⁵ / ₁₆	2 ¹³ / ₁₆	1	22.70	4200
16	1	1/2 x 2 ¹ / ₂	1/4 x 2 ¹ / ₂	15 ¹ / ₄	25	13 ¹ / ₂	3 ³ / ₈	1	25.38	4600
18	1	5/8 x 3	3/8 x 3	17 ¹ / ₂	27 ¹ / ₂	15 ¹ / ₈	3 ³ / ₄	1 ¹ / ₄	47.00	4800
20	1 ¹ / ₄	5/8 x 3	3/8 x 3	18 ¹ / ₂	29 ¹ / ₂	16 ³ / ₈	3 ³ / ₄	1 ¹ / ₄	50.50	4800
24	1 ¹ / ₄	5/8 x 3	3/8 x 3	20 ³ / ₄	34	18 ⁵ / ₈	4	1 ¹ / ₄	58.00	4800
30	1 ¹ / ₄	3/4 x 3	3/8 x 3	26 ⁵ / ₈	43	24	5 ³ / ₁₆	1 ¹ / ₄	75.00	6000

