



FIG. 535

Adjustable Pipe Saddle Support



SERVICE: For general piping running close to the floor.
MATERIAL: Carbon Steel or 304/316 Stainless Steel
FINISH: Black or Hot-Dip Galvanized
STANDARDS: MSS SP-58 Type 38
ORDERING: Specify figure number, pipe size, L dimension, material and finish. (Unit consists of saddle, nipple and reducer. Gussets will be added to supports for pipe sizes 8" and above. Welded base plate and pipe must be ordered separately.)

PIPE SIZE	PIPE SIZE A	B	C	D	DIMENSION E		WEIGHT EACH, LBS.	
					MIN.	MAX.	SADDLE ONLY	WITH REDUCER
2½	2½	3 ⁷ / ₁₆	8	1½	8	13	4.14	7.44
3	2½	3 ¹¹ / ₁₆	8	1½	8¼	13¼	4.40	7.70
4	3	4 ³ / ₁₆	10	2½	9¼	14	5.83	13.39
5	3	4 ¹³ / ₁₆	10	2½	10	14¾	6.48	14.04
6	3	5 ⁷ / ₁₆	10	2½	10½	15¼	10.24	17.80
8	3	6 ¹⁵ / ₁₆	10	2½	11¾	16½	13.16	20.72
10	3	8 ⁷ / ₁₆	10	2½	13½	18¼	17.23	24.79
12	3	9 ¹⁵ / ₁₆	10	2½	15	19¾	22.56	30.12
14	4	10 ¹⁵ / ₁₆	10	3	16¼	20¾	29.20	42.55
16	4	12 ³ / ₈	10	3	17¾	22¼	33.53	46.88
18	6	13 ⁷ / ₈	12	4	19½	24	52.83	74.78
20	6	15 ³ / ₈	12	4	21	25½	56.96	78.91
24	6	17 ¹⁵ / ₁₆	12	4	23¾	28¼	78.92	100.87
30	6	21 ⁵ / ₁₆	12	4	27	31½	90.40	112.35
36	6	24½	12	4	30¼	34¾	107.92	129.87

