



- FIG. 610**
- FIG. 615**
- FIG. 620**

## C-Clamp

### C-Clamp w/ Locknut

### C-Clamp Retaining Strap

**SERVICE:** For attaching to I-beams and wide flange beams where thickness does not exceed 3/4". Flange thickness may not exceed 5/8" when clamp is used with a retaining strap.

**MATERIAL:** Carbon Steel or 304/316 Stainless Steel

**FINISH:** Black or Electro-Galvanized

**STANDARDS:** MSS SP-58 Type 23, FS WW-H-171E Type 23

**APPROVALS:** FM (FIG. #615 and FIG. #610 with FIG. #620)

**ORDERING:** Specify figure number, rod size, material and finish.





FIG. #610 FIG. #615

FIG. #	C-CLAMP	ROD SIZE B	C	D	F	MAX PIPE SIZE	WEIGHT PER EACH, LBS.	MAX. REC. LOAD, LBS.
610	Standard	3/8	2 3/8	2 3/8	3/4	4	0.38	400
610	Standard	1/2	2 3/8	2 5/16	3/4	4	0.38	500
610	Standard	5/8	2 3/8	2 5/16	3/4	5	0.56	550
610	Standard	3/4	2 5/16	2 1/4	3/4	6	0.60	630
615	With Lock Nut	3/8	2 3/8	2 3/8	3/4	4	0.40	400
615	With Lock Nut	1/2	2 3/8	2 5/16	3/4	4	0.40	500
615	With Lock Nut	5/8	2 3/8	2 5/16	3/4	5	0.60	550
615	With Lock Nut	3/4	2 5/16	2 1/4	3/4	6	0.68	630

FIG. #620 L	WEIGHT PER EACH, LBS.
4 1/2	0.21
6	0.30
8	0.36
10	0.45
12	0.54
14	0.62

